



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

MAN TGS 41.440 BB 8x4 with MEILLER 16.5 cbm rear tipper – NEW

Code	Designation
001AA	steering arrangement, left
005UH	wheelbase 1795+2505+1400 mm
006CI	rear frame overhang 800 mm
018KG	Motor D2066LF36 - 440 PS / 324 KW EURO4 - 2100 Nm C-R OBD+NOx-S.
02AAB	instrument panel kmh 'Base-Line'
022WV	gearbox ZF 16 S 252 OD with ZF intarder
023CT	fuel tank 300l right
025ML	front axle VO-09/VO-09 straight
026EF	front springs parabolic 9,5 t
027AN	radiator and intercooler for up to 35 degrees ambient temperature
028FP	rear springs parabolic 16 t
028PA	Anbau Doppelachse
03KAA	fuel tank fitted
030EE	steering wheel with height and inclination adjustment
032AB	MAN BrakeMatic (electronic brake system)
034EC	brake shoe width for rear axle 220 mm
034MH	hub-reduction rear axle HPD-1382/ HP-1352
035KL	planetary axle ratio i = 4.00
037AC	with differential lock in rear axle
038GH	disc wheels 10 hole 11.75-22.5 on 1st FA TL
038JH	disc wheels 10-hole 11.75-22.5 on 2nd front axle TL
038PG	disc wheels 10-hole 9.00-22.5 on 1st RA TL
038RG	disc wheels 10-hole 9.00-22.5 on 2nd RA TL
042DF	Digitaler Fahrtschreiber; Fabrikat SIEMENS
05NAE	front panel unlockable from inside
050NN	M cab 2240mm wide, 1880mm long
052XA	without stowage boxes
058BA	seat coverings in standard quality
058NH	driver's seat, high-comfort, with air suspension
059NA	co-driver's seat static, with longitudinal + seat back adjustment
064AC	two additional vehicle keys
080AF	door interior panelling fabric
116AE	visco fan
118MA	EDC engine regulation
122QH	PTO NH/1C without flange f=0.91/1.09 right side, horizontal
123CC	strainer for fuel tank
124AL	fuel filter
124AM	additional fuel filter with water trap, make SEPAR
124EA	fuel filter heating
142AF	calibrate tachograph
153KC	air conditioning system AC R134A with automatic temperature control without CFHC
159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
194AZ	operator's manual in GREEK
201AS	air intake raised with dry air filter
201FA	fine dust and pollen filter
205AN	air compressor 1-cylinder, 360 ccm
206EY	exhaust on rh side with tail pipe to rear
208AK	exhaust valve brake
210AA	flame starting system

www.pktrucks.com



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

211FT	single-disc clutch MFZ 430 reinforced
227AC	rear axle breather upswept
230AH	rear underride guard, round
230XW	without front underride guard
230YX	without lateral underride guard
233EM	3-part steel bumper
234AX	towing coupling ROCKINGER SK5
236AF	cross member for trailer coupling
241AC	without platform mounting brackets
245XX	without spare wheel holder
256AF	steering wheel lock with immobiliser
256EA	emergency steering pump
257LM	multifunction steering wheel for 'M' cab
258HA	anti-lock braking system (ABS)
259CA	disc brake for front axle
259CE	drum brake for rear axle
262XX	without brake connection on frame end
263AF	asbestos-free brake linings
272FA	entry lighting for driver and co-driver
280EC	fly mesh guard before radiator
281AB	medium-height design
283FB	cab mounts on coil springs for 'M' cab
303AA	tank cap lockable - 1 cap w/o vent
309AA	beam throw regulator
310EE	halogen twin headlights H7 for right-hand traffic
318AA	marker lamps
318AK	lateral marker lights
319AR	reading lamp for driver
321EC	central locking
324AC	two-tone horn, electric
325AA	MAN Tronic (on-board computer)
325EA	Language 1 'German' for display in instrument panel
325FY	language 2 'Greek' for display in instrument panel
326XY	without 24 V socket at frame end
329CT	2 batteries, 12V 175Ah
329ER	battery box up to 175Ah
331CB	alternator 28V 80A 2240 W
339FP	Anzeige in Instrumententafel für Betriebsdaten
345AV	speed limiter electronic 85 km/h
345EA	cruise control
346CA	charging pressure indicator
350NL	radio MAN BasicLine 24V
362AH	stabilizer on both rear axles
363AA	stabilizer for front axle
370CM	air dryer
373AD	antifreeze down to -25 degrees
376XH	without mattress for lower bunk
376XK	without mattress for upper bunk
376XL	without bunk for 'M' and 'C' cab
378XE	without pillow
380AC	windscreen of laminated glass tinted
380CA	door windows tinted
381AA	cab rear wall without windows
381XC	without curtain before bunks
381YA	without all-round curtain for C/M cab

www.pktrucks.com



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

384CD	safety belt display, driver's side side
385AT	windows tinted behind B-post
386AS	mechanical sliding roof
387AF	electric door window lifters for driver and co-driver
388AH	roller blind for windscreen, mechanical
388AK	sun shade in front of windscreen
389AC	handles left and right (on B-post)
389AD	handles left and right (on A-post)
390AO	coolbox
390CU	1 Schublade ausziehbar im Armaturenbrett-Mittelteil
390XN	without waste paper bins between the seats
392AH	kerb mirror, right
392CL	EU front mirror on co-driver's side
392CZ	Rückspiegel heizbar und elektrisch verstellbar, Weitwinkelspiegel heizbar
392HA	mirror brackets for body width 2500-2600 mm width 2500 mm
400AH	mudflap front
401CY	synthetic mudguards, 3-part, with mud flaps
401EL	3-part synthetic mudguards for 2nd front axle
404AP	spray reducer
405AC	first-aid kit
405AK	hazard-warning sign
405AR	hazard-warning lamp
407AH	jack 12 t
411AF	2 chocks
534KY	permissible front axle load 2 x 9000 kg
538AE	plastic floor and engine tunnel covering
542BA	low-noise certification for Austria and L plate
542FC	anti-noise package 80 dB (92/97EEC)
542IZ	confirmation for international registration
600AC	Fittings for right-hand traffic
798WK	vehicle can be registered only as off-road vehicle to directive 70/156/EEC; note body
LQW01	chassis in water-based paint
LVS01	chassis graphite black RAL 9011 matt
LVS02	wheels White aluminium acrylic RAL 9006
LVS03	cab Pure white RAL 9010
80001	2 Dunlop 385/65R22,5 SP 382 TL 160
80002	2 Dunlop 385/65R22,5 SP 382 TL 160
90001	4 Dunlop 315/80R22,5 SP 482 TL 156
90002	4 Dunlop 315/80R22,5 SP 482 TL 156

Weights:

Gross weight:	41000
1st front axle:	9000
2nd front axle:	9000
1st rear axle:	13000
2nd rear axle:	13000

The prescribed data corresponds to current manufacturing regulations at the time of expression. Subject to change.

www.pktrucks.com