



# pk trucks holland

Showroom: Graanweg 2 (M200)  
4782 PP Moerdijk  
The Netherlands

Tel. : +31 168 382 032  
Fax : +31 168 382 023  
E-mail: pktrucks@pktrucks.com

---

## **LODICO 3-axes extendable flatbed semi-trailer - NEW**

Type: 3-axes extendable flatbed semi-trailer (single tire)  
Model: THT9502T JPS

### **DIMENSIONS:**

Overall Length: Retracted position: 12,404 mm  
Extended position: 18,404 mm  
Overall Width: 2,480 mm  
Frame Height: 1,592 mm  
Front overhang: 1,000 mm  
Landing Leg Setting: 2,500 mm  
Wheel base: 7,160 (13,160) +1,310+1,310 mm  
Kin Pin Plate Height : 1,301 mm  
Front Fitting Radius: 1,600 mm  
Rear Tractor Clearance Radius: 2,420 mm

### **WEIGHTS:**

#### **RETRACTED POSITION:**

Tare Weight : 9,400kg  
Payload: 40,000kg  
G.V.W.R.: 49,400kg  
Kingpin Weight : 18,360kg  
Axles Weight : 31,040kg  
(The tires overload approx. 15%)

#### **EXTENDED POSITION:**

Tare Weight : 9,400kg  
Payload: 35,000kg  
G.V.W.R.: 44,400kg  
Kingpin Weight : 18,130kg  
Axles Weight : 26,270kg

### **RUNNING GEAR & FRAME:**

Suspension: Under mount tri-axle suspension with equalizer; 7-leaf spring;  
39,000Kg capacity.

Axle: FUWA square axle, 13 ton capacity/set.

Wheel: 11.75-22.5, 10 holes steel Disc wheel. 6pcs. Made in china.

Tire: 385/65R22.5 tires. 6pcs. Made in china.

King Pin: JOST 2" bolted type; Model: JOST KZ1012.

Platform: Extendable loading platform with semi-automatic, pneumatic locking.

---

# www.pktrucks.com



# pk trucks holland

Showroom: Graanweg 2 (M200)  
4782 PP Moerdijk  
The Netherlands

Tel. : +31 168 382 032  
Fax : +31 168 382 023  
E-mail: pktrucks@pktrucks.com

---

2.75mm thick checker plate.  
No floor in extended area.  
Lock: 12 sets twist locks.  
AII locks are retractable type.

**AIR SYSTEM:** (COMPLY WITH THE THT STANDARDS)

Brake: Dual line pneumatic brake system, Haldex brake valve, without ABS.  
Brake chamber: Type 30/30 spring brake chamber on front axle.  
Type 30 brake chamber on middle and rear axles.

**ELECTRICAL SYSTEM:**

Voltage: 24 Volt.  
Receptacle: 7 way.  
Front Marker Lamp: white  
Side flasher lamp: amber  
Side Marker Lamp: amber  
Rear Lamp: red  
Turn Signal Lamp: amber

**LANDING LEGS:**

Leg: Two speed manual operation type with sand shoe; right handle. model: TSU CL25TA  
Rated Capacity: Static: 80 ton. Lifting: 25 ton.

**PAINTING & MARKING:**

Painting: Comply with the THT standard.  
Color: Comply with the customer's request.  
Marking: Comply with the THT standard.

**OTHER:**

Side guard: 1 set.  
Tool box: 1 pcs  
Spare tire carriers: 2 pcs  
In retracted position, the maximum load of this semi-trailer is 40,000kg.  
Then the tires overload approx. 15% .  
In extended position, the maximum load of this semi-trailer is 35,000kg.  
Tractor: 6X4, the fifth wheel height is 1400mm .  
AII the details .are not mentioned above should comply with the THT standards.

---

# www.pktrucks.com