



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

MAN TGA 33.400 BB-WW 6x4 chassis cabin - NEW

pk trucks id: ma2013



Technical extent of delivery

Code	Designation
001AA	steering arrangement, left
005OU	wheelbase 4500+1400 mm
006PK	rear frame overhang 2500 mm
018SI	engine D2066LF06 - 400 hp / 294 KW EURO2 - 1900 Nm Common-Rail
02AAB	instrument panel kmh 'Base-Line'
022GE	gearbox ZF 16 S 252 OD
023EH	fuel tank 400l right
025MK	front axle VO-09 straight
026EC	front springs parabolic 8.0 t
027AX	extended radiator and intercooler over 35 degrees ambient temperature
028EC	rear springs parabolic 13 t
028PA	Anbau Doppelachse
03KAA	fuel tank fitted
030EE	steering wheel with height and inclination adjustment
032AB	MAN BrakeMatic (electronic brake system)
034EC	brake shoe width for rear axle 220 mm
034MH	hub-reduction rear axle HPD-1382/ HP-1352
035KL	planetary axle ratio i = 4.00
037AC	with differential lock in rear axle
038GG	disc wheels 10 hole 9.00-22.5 on 1st FA TL
038PG	disc wheels 10-hole 9.00-22.5 on 1st RA TL
038RG	disc wheels 10-hole 9.00-22.5 on 2nd RA TL
038TG	disc wheel 10-hole 9.00-22.5 as spare wheel TL
042CY	EC tachograph electronic, automatic, 2 drivers (no EU-approval since 2006)
05NAE	front panel unlockable from inside
050NN	M cab 2240mm wide, 1880mm long
052XA	without stowage boxes
058BA	seat coverings in standard quality
058NE	driver's seat static, longitudinal, seat back and height adjustment
059NA	co-driver's seat static, with longitudinal + seat back adjustment
080AE	door interior panelling washable
116AE	visco fan
118AP	engine no. also on crankcase
118MA	EDC engine regulation

Weights:

Gross weight:	28000
1st front axle:	8000
2nd front axle:	0
3rd front axle:	0
Leading axle:	0
1st rear axle:	13000
2nd rear axle:	13000
Trailing axle:	0

www.pktrucks.com



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

119ER	sector-specific parametrisation for concrete pump vehicles (working speed control)
121NA	without heating for gearshift
122QH	PTO NH/1C without flange f=0.91/1.09 right side, horizontal
123AC	guard plate for 1 tank
123CC	strainer for fuel tank
124AL	fuel filter
124AM	additional fuel filter with water trap, make SEPAR
125CM	PTO NMV221 f=1.5
142AF	calibrate tachograph
153KC	air conditioning system AC R134A with automatic temperature control without CFHC
159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
194CC	operator's manual in ARABIC
194EA	additional operator's manual in ENGLISH
196XA	without sticker on front panel
201AR	air intake upswept with dry air filter / precleaner
201EM	air filter element with safety element for heavy-duty operation
201FA	fine dust and pollen filter
203ER	control module for external data exchange (KSM) with body functions
205AN	air compressor 1-cylinder, 360 ccm
206ET	exhaust on lh side with tail pipe towards rear
208AK	exhaust valve brake
210XX	without flame starting system
211FF	single-plate clutch MFZ 430
212AA	gearbox shift lock, pneumatic
214CG	output flange 120 mm for NMV cross-serrated (4-hole)
227AC	rear axle breather upswept
230AH	rear underride guard, round
230XW	without front underride guard
230YX	without lateral underride guard
233EM	3-part steel bumper
236AF	cross member for trailer coupling
241AC	without platform mounting brackets
245AE	spare-wheel holder on left side
256AF	steering wheel lock with immobiliser
258HA	anti-lock braking system (ABS)
259CA X	disc brake for front axle
259CE	drum brake for rear axle
262CN X	brake system for concrete pump chassis without trailer brake connection
263AF	asbestos-free brake linings
265AF X	parking brake with pneumatic application of front wheel brakes

www.pktrucks.com



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

272FA	entry lighting for driver and co-driver
278AA	compressed-air connection for auxiliary consumers in body
280EU	stoneguard grille in front of radiator
280HL	provision for engine start and stop at frame end
281AB	medium-height design
283FB	cab mounts on coil springs for 'M' cab
284LT	special permit must be requested from registration authorities by sales centre
303AA	tank cap lockable - 1 cap w/o vent
309AA	beam throw regulator
310EE	halogen twin headlights H7 for right-hand traffic
311AA	protective grille for headlights headlights
311BA	Note: protective grilles for headlights have no EU approval
318AA	marker lamps
318AK	lateral marker lights
319AR	reading lamp for driver
321EC	central locking
324AC	two-tone horn,electric
325AA	MAN Tronic (on-board computer)
325EE	language 1 'French' for display in instrument panel
325FC	language 2 'English' for display in instrument panel
326CK	trailer socket for anti-skid system on frame end
326XY	without 24 V socket at frame end
327AF	battery main switch, mechanical
329CW	2 batteries, 12V 225 Ah
329ES	battery box up to 225Ah
331HC	alternator 28V 110A 3080W
337AH	oil pressure gauge
337AK	oil temperature gauge
339AN	crankshaft revolutions counter
339FA	time in instrument panel (trip data)
343AN	acoustic warning system for engaged reverse gear at frame end
345AV	speed limiter electronic 85 km/h
345EA	cruise control
346AA	service meter
346CA	charging pressure indicator
350XX	without radio system
362AH	stabilizer on both rear axles
363AA	stabilizer for front axle
370CM	air dryer
373AD	Antifreeze effective down to -27 degrees
376XH	without mattress for lower bunk
376XK	without mattress for upper bunk

www.pktrucks.com



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

376XL	No bunks for 'M', 'C', 'DK' cabs
378XE	without pillow
380AC	windscreen of laminated glass tinted
380CA	door windows tinted
381AS	cab rear wall with 2 tinted windows,centre and right
381XC	without curtain before bunks
381YA	without all-round curtain for C/M cab
384CD	safety belt display, driver's side
385AT	side windows tinted behind B-post
386AS	mechanical sliding roof
387AF	electric door window lifters for driver and co-driver
388AH	roller blind for windscreen, mechanical
389AC	handles left and right (on B-post)
389AD	handles left and right (on A-post)
390AT	oddments box
390XN	without waste paper bins between theseats
392AK	rear-view mirror(s) heatable and electrically adjustable
392AR	kerb mirror, right, heated and electrically adjustable
392AS	wide-angle mirror, right, heatable and electrically adjustable
392AX	wide-angle mirror, left, heated and electrically adjustable
392CC	mirror engraved in Arabic
392HA	mirror brackets for body width 2500-2600 mm width 2500 mm
392XJ	Without front mirror on co-driver's side
394FM	1 Fire extinguisher 2 kg multilingual (English/German/Dutch)
400AH	mudflap front
401AF	temporary transport mudguards
401CW	deletion of plastic mudguards
404AP	spray reducer
405AC	first-aid kit
405AU	2 breakdown warning signs loose
405CP	20 m tyre inflator hose with pressure gauge
405FD	2 warning flashers loose
407AH	jack 12 t
411AA	1 chock
411AC	2nd chock
434AF	cigar lighter and socket
434AK	hand lamp with cable (10m)
434ES	dashboard in standard version
523AC	signs in English
523AM	signs additionally in Arabic
524IS	load variant 28000 kg
534FA	permissible front axle load 8000 kg
535KS	permissible rear axle load 2 x 13000 kg

www.pktrucks.com



pk trucks holland

Showroom: Graanweg 2 (M200)
4782 PP Moerdijk
The Netherlands

Tel. : +31 168 382 032
Fax : +31 168 382 023
E-mail: pktrucks@pktrucks.com

538AE	plastic floor and engine tunnel covering
542BC	COP document
542FX	anti-noise measures are not in accordance with EU standard
542HS	aprons in wheel houses to prevent soiling of the engine
542IZ	confirmation for the application for a German export license into non-EU-countries
600AC	Fittings for right-hand traffic
796BB	Order conversion at a qualified conversion provider of MAN Nutzfahrzeuge AG by Central Sales
798CH	retrofitting in SN Umbauarbeiten für Putzmeister BSF 32/36 gemäß Vorgaben.
798TX	Target country and body type
LQW01	chassis in water-based paint
LVS01	chassis graphite black RAL 9011 matt
LVS02	wheels White aluminium acrylic RAL 9006
LVS03	cab Pure white RAL 9010
80001	2 Michelin 315/80R22,5 XZY2 TL 156
90001	4 Michelin 315/80R22,5 XDY3 TL 1
90002	4 Michelin 315/80R22,5 XDY3 TL 1
90004	1 Michelin 315/80R22,5 XZY2 TL 156

www.pktrucks.com