



# pk trucks holland

Showroom: Graanweg 2 (M200)  
4782 PP Moerdijk  
The Netherlands

Tel. : +31 168 382 032  
Fax : +31 168 382 023  
E-mail: pktrucks@pktrucks.com

---

## TATA Xenon 2.2L DICOR 4x4 pick up with double cabin – NEW

### THE BEAUTY

Smart, stylish, elegant, distinctive, imposing, modern and aggressive. The new Xenon is truly a treat for your eyes. But don't take our word for it. Take a test-drive and you'll know why it demands your attention.

### THE BEAST

Sturdy, powerful and hardworking. To the new Xenon, performance comes naturally. With the beastly 2.2 litre, Dicor diesel engine, it churns out 140 ps of raw power. Packed with features, the Xenon challenges your adrenaline and commands to be driven to be believed.

### TATA XENON 4x4 TECHNICAL SPECIFICATIONS:

<b>ENGINE</b>	Tata 2.2L DICOR Euro-III, Euro-IV
Type	Water-cooled, Direct Injection Common Rail (DICOR), Turbocharged Intercooled Diesel Engine with EGR
No. of Cylinders	4 (inline)
Bore x Stroke	85 mm x 96 mm
Capacity	2179 cc
Max. Engine Power	103 KW, 140 Hp @ 4000 rpm
Max. Torque	320 Nm @ 1700 - 2700 rpm
Compression Ratio	17.2:1
Firing Order	1-3-4-2
Max. Engine Oil Capacity	7.5 Lit.
Min Engine Oil Capacity	5.5 Lit.
Dry Weight of Engine	235 Kg
<b>CLUTCH</b>	Single plate, dry friction, diaphragm type
Outer Diameter of Clutch Lining	240 mm
Friction Area	503 Sq. Cm.
<b>GEAR BOX</b>	G-76-5/4.1 with Overdrive, Synchronesh on all gears
No. of Gears	5 Forward, 1 Reverse
Gear Ratios	1st: 4.1, 2nd: 2.22, 3rd: 1.37, 4th: 1.00, 5th: 0.77, R: 3.75
Transfer Case	Electrical shift arrangement
Drive Options	4x2 Ratio: 1:1, 4x4 High Ratio: 1:1, 4x4 Low Ratio: 1:2.48
<b>AXLES</b>	
Rear Axle	Single reduction, Salisbury Type with Hypoid Gears, Semi-Floating Axle Shafts & Limited Slip Differential
Rear Axle Ratio	3.73 (41/11)
Front Axle	Independently Suspended
Front Axle for 4x4 Variants	Automatic Hub Locks
Front Axle Ratio	3.73 (41/11)
<b>STEERING</b>	
Power steering Ratio	Tilt able power steering, 400 mm diameter, 4 spoke steering wheel 18.2:1, 18.9:1 (alternate)
<b>BRAKES</b>	
Front Brakes	Vacuum assisted independent hydraulic brakes on front & rear wheels through tandem master cylinder and tandem booster. Camshaft driven vacuum pump 281 mm diameter ventilated disc brakes with twin pot calipers
Rear Brakes	282 mm diameter drum brakes with auto adjuster LCRV Load conscious pressure reducing valve on rear brakes

---

# www.pktrucks.com



# pk trucks holland

Showroom: Graanweg 2 (M200)  
4782 PP Moerdijk  
The Netherlands

Tel. : +31 168 382 032  
Fax : +31 168 382 023  
E-mail: pktrucks@pktrucks.com

## Parking Brakes

Cable operated mechanical linkage acting on rear wheels

## SUSPENSION

Front Suspension  
Rear Suspension  
Shock Absorbers  
Antiroll Bar

Double wishbone type with torsion bar  
Parabolic leaf springs  
Hydraulic double acting telescopic type at front & rear  
At Front

## WHEELS & TIRES

Tires  
Tire Pressure  
Wheel Rims  
Spare Wheel

205 R 16 C 106 S Tubeless Radials  
Unladen: Front: 29 psi; Rear: 29 psi Laden: Front: 29 psi; Rear: 44 psi  
5.5 J x 16 (Alloy Wheels on Premium Versions)  
Steel Wheel Rim

## FUEL TANK

65 litres

## ELECTRICALS

Alternator Capacity  
Battery

12 V  
125 Amperes  
12 V, 80 Ah MF

## PERFORMANCE

Max. Speed  
Max. Grade ability

160 Kmph  
41% 90% (4x4 Mode)

## COLOR

ARCTIC WHITE

## XENON FEATURES & TRIM LEVELS: STANDARD FEATURES

Cigarette Lighter  
12V Mobile Charging Point  
Spoiler on Wiper Blade  
Roof Lamp  
Engine Compartment Lamp  
Ash Tray  
Coin Box  
Remote Fuel Lid Opening  
Cup Holders  
Rear Tubular Bumper

## XENON FEATURES & TRIM LEVELS:

### OPTION LIST

Wheel Type	Alloy Wheels (4 Wheels)
Ventilation	HVAC
Tail Gate Handle	Body Colored
Door Trim	Fabric Finished
Outer Rear View Mirror	Electrically operated and heated
Window Winding	Electrically operated
Fog Lamps	Front and Rear
Music System	AM/FM Radio and CD Player
Radio Antenna	
Central Locking	
Child Lock (for Crew Cab only)	
Immobilizer	
Steering Wheel	Leather Covered

---

# www.pktrucks.com



# pk trucks holland

Showroom: Graanweg 2 (M200)  
4782 PP Moerdijk  
The Netherlands

Tel. : +31 168 382 032  
Fax : +31 168 382 023  
E-mail: [pktrucks@pktrucks.com](mailto:pktrucks@pktrucks.com)

---

## XENON DIMENSIONS:

2.2L DICOR	
Wheelbase (mm)	3150
Front Track (mm)	1571
Rear Track (mm)	1571
Overall Length (mm)	5125
Max. Width (mm)	1860
Front Overhang (mm)	870
Rear Overhang (mm)	1105
Overall Height Laden (mm)	1730
Overall Height Un-Laden (mm)	1765
Minimum Turning Circle Diameter (m)	12
Minimum Turning Clearance Diameter (m)	12.9
Ground Clearance (mm)	200
Kerb Weight (Kg)	1575
GVW (Kg)	2950
Payload (Kg)	1375
GCW (Kg)	4950
Towing Capacity Unbraked Trailer (Kg)	750
Towing Capacity Braked Trailer (Kg)	2000
Max. Permissible FAW (Kg)	1400
Max Permissible RAW (Kg)	1800
Loading Area (LxBxH) (mxmxm)	1.43 x 1.41 x 0.40

## Offering a "Perfect Balance":

The XENON is sturdy and powerful to work hard for you, and offers aggressive styling to make your presence felt on the road.

## The Xenon delivers:

- Contemporary styling
- Better engine technology and power
- Superior interior comfort and convenience
- Better ride and handling

Thereby becoming an ideal "dual use" vehicle.

---

# [www.pktrucks.com](http://www.pktrucks.com)