

MAN TGS 33.360 6X4 BB-WW

Code	Designation
001AA	steering arrangement, left
005NK	Wheelbase 3600+1400 mm
006CI	rear frame overhang 800 mm
018IZ	Engine D2066LF48 - 360 HP / 265 KW EURO3 - 1800 Nm common rail
02AAE	instrument panel km/h 'High-Line'
021GP	Transmission software for road-going use (TipMatic PROFI)
022GW	gearbox ZF 12 AS 2330 OD MAN TipMatic
023CT	fuel tank 300l right
025MK	front axle VO-09 straight
026EC	front springs parabolic 8.0 t
027AP	radiator and intercooler for over 35degrees ambient temperature
028EC	rear springs parabolic 13 t
028PA	Fit tandem axles
029GC	Propshafts for high load profile
03KAA	fuel tank fitted
030EE	steering wheel with height and inclination adjustment
032AB	MAN BrakeMatic (electronic brake system)
034EC	brake shoe width for rear axle 220 mm
034MH	hub-reduction rear axle HPD-1382/ HP-1352
035LF	Planetary axle ratio $i = 4.33$
037AC	with differential lock in rear axle
038GG	disc wheels 10 hole 9.00-22.5 on 1stFA TL
038PG	disc wheels 10-hole 9.00-22.5 on 1stRA TL
038RG	disc wheels 10-hole 9.00-22.5 on 2ndRA TL
038TG	disc wheel 10-hole 9.00-22.5 as spare wheel TL
042XY	without electronic tachograph
05NAE	front panel unlockable from inside
050NN	M cab 2240mm wide, 1880mm long
052XA	without stowage boxes
058BA	seat coverings in standard quality
058NH	driver's seat, high-comfort, with air suspension
059NA	co-driver's seat static, with longitudinal + seat back adjustment
064AC	two additional vehicle keys
080AE	door interior panelling washable
116AE	visco fan
116AZ	Fan control for use in hot countries
118AC	air deflector to stop dust swirling
118DA	Cover to protect charge air cooler from cold
118EK	Short mounting base (engine only)

118MA	EDC engine regulation
119EH	General PTO parameterisation
120KP	PTO on flywheel side with pump connection spline profile DIN ISO 14- 8x32x36 f=1.233
123CC	strainer for fuel tank
124AT	additional fuel filter heated with water trap
124EA	fuel filter heating
153KA	air conditioning system AC R134A without CFHC
159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
172EP	red-and-white warning stripes on doors and air deflectors
201AR	air intake upswept with dry air filter / precleaner
201EM	Air filter cartridge with safety insert for heavy-duty deployment
201FA	fine dust and pollen filter
203EK	connection for external engine speedcontrol (ZDR)
203ER	Control module for external data exchange (customer-specific control module) with body functionality
205AN	air compressor 1-cylinder, 360 ccm
206ET	exhaust on lh side with tail pipe towards rear
208XD	without exhaust valve brake (EVB)
210AA	flame starting system
211FF	single-plate clutch MFZ 430
227AC	rear axle breather upswept
230AH	rear underride guard, round
230XW	Without front underride guard
230YX	without lateral underride guard
233EM	3-part steel bumper
234AX	towing coupling ROCKINGER SK5
236AF	cross member for trailer coupling
241AC	without platform mounting brackets
245XX	without spare wheel holder
256AA	steering wheel lock
258HA	anti-lock braking system (ABS)
259CA	disc brake for front axle
259CE	drum brake for rear axle
262AC	brake connection 2-line
272FA	Entry lighting for driver and co-driver
278AA	compressed-air connection for auxiliary consumers in body
280EC	Fly mesh guard before radiator
281AB	medium-height design
283FB	Cab mounts on coil springs for 'M' cab
284NK	For use in Nordic countries and Eastern Europe
303AX	Lockable tank fastener - 1 u. ventilated for master key system
310EE	Halogen twin headlights H7 for right-hand traffic
318AA	marker lamps

318AK	lateral marker lights
319AR	reading lamp for driver
321EC	central locking
324AC	Two-tone horn,electric
325AA	MAN Tronic (on-board computer)
326CK	trailer socket for anti-skid system on frame end
326CW	7+7-pin 24 V trailer socket at end of frame
326FZ	Socket in cab 12V 2-pole and 24V 2-pole
327AF	battery main switch, mechanical
329CW	Two 12-V 225-Ah batteries
329ES	Battery box up to 225 Ah
329HC	Maintenance sign for batteries - 'maintenance-free'
331CY	28V three-phase alternator 120A 3360W Longlife Eco
339FP	Display on the dashboard for operating data
343AN	Acoustic warning system at end of frame for engaged reverse gear
345AU	Maximum electronic speed limitation 89 km/h
345EA	cruise control
346CA	charging pressure indicator
350LK	CB radio antenna on cab roof
350NL	Radio MAN BasicLine 24V
351AF	preparation for radiotelephone
352CF	2 halogen revolving beacons on cab roof left and right
352WS	Revolving beacon, yellow
362AH	Stabiliser on both rear axles
363AA	Stabiliser for front axle
370CR	air dryer, heated
373AE	antifreeze effective down to -35 degrees
376XH	Without Mattress for lower bunk
376XK	Without Mattress for upper bunk
376XL	No bunks for 'M' , 'C', 'DK' cabs
380AC	windscreen of laminated glass tinted
380CA	door windows tinted
381AA	cab rear wall without windows
381XC	Without curtain before bunks
381YA	Without all-roand curtain for C/M cab
384CD	Safety belt display, driver's side
385AT	Side windows tinted behind B-post
386AS	Mechanical sliding roof
387AF	Electric door window lifters for driver and co-driver
388AH	Roller blind for windscreen, mechanical
389AC	handles left and right (on B-post)
389AD	handles left and right (on A-post)

Weights:

Gross weight: 33000

1st front axle: 7500

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 13000

2nd rear axle: 13000

Trailing axle: 0