

Model : TGM 18.240 4X2 BB

Vehicle model: TGM 18.240 4X2 BB
 Basic vehicle L N08 FG 12

Code	Designation
000AA	Non-variable parts
001AA	steering arrangement, left
005CF	Wheelbase 4125 mm
006MN	rear frame overhang 2125 mm
018MK	engine D0836LFL40 - 240 hp / 176 kW EURO3 - 925 Nm Common Rail
02AAB	instrument panel kmh 'Base-Line'
022IP	Transmission ZF 9S-1110 DD
023IK	Fuel tank 180 l right
025MU	front axle VOK-07 dropped
026EA	front springs parabolic 7.1 t
027AC	radiator and intercooler
028EB	rear springs parabolic, 11.5 t
03KAA	fuel tank fitted
030AC	hydraulic steering
030EE	steering wheel with height and inclination adjustment
032AB	MAN BrakeMatic (electronic brake system)
034NH	hypoid rear axle HY-1133
035ET	Hypoid axle ratio $i = 3.70$
037XX	without differential lock in rear axle
038GC	disc wheels 10 hole 8.25-22.5 on 1stFA TL
038PC	disc wheels 10-hole 8.25-22.5 on 1stRA TL
038TC	disc wheel 10-hole 8.25-22.5 as spare wheel TL
042XY	without electronic tachograph
050NK	'C' cab, 2,240 mm wide and 1,620 mm long
052XA	without stowage boxes
058BA	seat coverings in standard quality
058NA	driver's seat static, longitudinal adjustment and seat back adjustment
059HC	Static co-driver's seat with storagebox
064AC	two additional vehicle keys
080AE	door interior panelling washable
116AE	visco fan
118MA	EDC engine regulation
119EH	General PTO parameterisation
121EH	neutral pos. switch
122HQ	Power take-off NH/1C without flange $f=0.72$
123CC	strainer for fuel tank
123CE	chain for tank cap
124AL	fuel filter
124AM	additional fuel filter with water trap, make SEPAR
124EA	fuel filter heating

142AF	calibrate tachograph
153KC	air conditioning system AC R134A with automatic temperature control without CFHC
157EB	'G' plate
194AB	operator's manual in English
201AE	dry air filter with prefilter
203ER	Control module for external data exchange (customer-specific control module) with body functionality
205AP	1-cyl. compressor 238 cc
206ES	exhaust on rh side with tail pipe towards frame centre
208AB	engine brake with additional actuation via brake pedal
208AK	exhaust valve brake
210XX	Without flame-start/jump-start system
211AD	clutch with 395 mm diameter
219AF	steering oil reservoir with dipstick
230AC	with underride guard at rear
230ER	front underride guard
230YX	without lateral underride guard
232HC	synthetic bumper
234AX	towing coupling ROCKINGER SK5
236CS	rear cross member for trailer coupling 160X100
241AE	body mounting brackets on frame
245AE	spare-wheel holder on left side
256AA	steering wheel lock
258HA	anti-lock braking system (ABS)
258HB	anti-spin regulator (ASR)
259CA	disc brake for front axle
259CB	disc brake for rear axle
262XX	without brake connection on frame end
278AE	Air filler connection at front
280BA	Equipment for hazardous goods to ADR, type AT
283FR	Cab mounts on coil springs for 'C' cab
303AX	Lockable tank fastener - 1 u. ventilated for master key system
309AA	Beam throw regulator
310EE	Halogen twin headlights H7 for right-hand traffic
318AA	marker lamps
318AK	lateral marker lights
319YX	without reading light
324AA	Single-tone horn, electric
325AA	MAN Tronic (on-board computer)
325EC	Language 1 'English' for display in instrument panel
325FE	Language 2 'French' for display in instrument panel
326XY	Without 12/24 V socket on end of frame
327AF	battery main switch, mechanical
329AC	2 batteries 12 V 88 Ah
329ED	Battery box lockable (without lock)
329HC	Maintenance sign for batteries - 'maintenance-free'
33VAC	engine capsule
331AB	Basic alternator
339FP	Display on the dashboard for operating data

343AZ	Warning buzzer in seven-chamber light when reverse gear engaged
345CV	Maximum electronic speed limitation 85 km/h
345XA	Without cruise control
348AA	Coolant level indicator in cab
350CB	Preparation for radio 24V
352ED	Preparation for additional cab lighting on cab roof
362AA	Stabiliser for rear axle
363AA	Stabiliser for front axle
370CM	air dryer
376XH	Without Mattress for lower bunk
376XK	Without Mattress for upper bunk
376XL	No bunks for 'M' , 'C' , 'DK' cabs
380AC	windscreen of laminated glass tinted
380CA	door windows tinted
381AP	Cab rear wall with 3 tinted windows
381XC	Without curtain before bunks
381YX	Without all-roand curtain
384CD	Safety belt display, driver's side
386XA	Without lifting roof
387AG	Mechanical door window lifters for driver and co-driver
388AB	Folding sunshade for driver and co-driver
388AK	sun shade in front of windscreen
389AC	handles left and right (on B-post)
389AD	handles left and right (on A-post)
390AX	storage compartment above windscreen
390CW	pigeon hole on rear wall lhs
390XX	without oddment box
392AH	kerb mirror, right
392AL	mechanical wide-angle mirror, right
392AT	mech. wide-angle mirror, left
392AY	rear view mirror, mech. adjustable
392CL	EU front mirror on co-driver's side
392HA	Mirror brackets for body width 2500-2600 mm width 2500 mm
396CC	windscreen washer electric
400AH	mudflap front
401AF	temporary transport mudguards
401CW	deletion of plastic mudguards
404AP	spray reducer
405AC	Bonding set, separate
405AK	hazard-warning sign
405AR	hazard-warning lamp
405CP	20 m tyre inflator hose with pressure gauge
407AN	Jack, 10 t
411AA	1 chock
434AF	cigar lighter and socket
434ES	dashboard in standard version
523AC	signs in English
538AE	plastic floor and engine tunnel covering
542BT	ADR inspection and certificate
542DE	Confirmation of conformity to EC Directives

542DM	Supplier declaration
542FC	anti-noise package 80 dB (92/97EEC)
542NC	Registration as N3 vehicle, (GVW > 12t)
600AC	Fittings for right-hand traffic
LQW01	chassis in water-based paint
LVS01	chassis graphite black RAL 9011 matt
LVS02	wheels White aluminium acrylic RAL 9006
LVS03	cab Pure white RAL 9010
80001	2 wahlweise 295/80R22,5 LENK-S+G TL
90001	4 wahlweise 295/80R22,5 LENK-S+G TL
90004	1 wahlweise 295/80R22,5 LENK-S+G TL

Weights:

Gross weight: 18000

1st front axle: 7100

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 11500