

TECHNICAL DESCRIPTION

SUBJECT: tank 20.000 l capacity for fuel transportation, with pumping unit and meter unit installed on MAN TGS 40.480 6x6 wheelbase 3900, with rear overhang extension and installation of rear underride bar with work platform

Tank with one compartment, 20.000 l capacity, built in carbon steel plates, 4 mm thick, with dimensions suitable to the chassis supplied.

TANK

- steel shells welded together and to the dished heads
- internal anti-sloshing baffles
- saddles shaped according to the tank section are supporting the tank by semi-elastic connections and connected to the truck chassis by bolted plates in the rear and springs in the front
- n.1 manhole with cover, diam. 500, complete with loading port and breathing valve
- n.1 dip stick level indicator
- n.1 bottom valve with pneumatic remote control
- n.1 access ladder to manhole and platform
- n.2 fire extinguishers with 9 kg of chemical powder in special holders
- n.2 pieces of flexible hoses, 3 m long with quick connections, placed in special lockable stainless steel carriers
- Equipotential copper connections between tank and vehicle chassis, set of warning signs for transportation of flammable fluids
- n.1 lockable metallic storage box for vehicle standard accessories
- mud guards for rear wheels

PUMPING AND METERING UNIT INSIDE A STAINLESS STEEL CASE POSITIONED ON THE REAR SIDE OF THE TANK

A positive displacement pump 500 l/min capacity, operated by the truck engine through a properly dimensioned hydraulic oil system, activated by the truck PTO. The PTO is pneumatically controlled from the driver's cab.

Suitable piping, gate valves and connections allow the tank loading, unloading and fuel transfer operations

Fuel meter complete with filter, partial and total measuring and with a flow rate of 500 l/min.

Reel with manual winding device with hand crank and 15 m of 1"1/2 hose and delivery gun.