

MAN TGS 41.400 8x4 BB-WW

Code	Designation
001AA	steering arrangement, left
005UR	Wheelbase 1795+4105+1400 mm
006DW	rear frame overhang 1000 mm
018SI	engine D2066LF06 - 400 hp / 294 KW EURO2 - 1900 Nm Common-Rail
02AAE	instrument panel km/h 'High-Line'
022WO	Gearbox ZF 16 S 253 OD
023EH	fuel tank 400l right
025MG	front axle VOK-09/VOK-09, dropped
026EF	front springs parabolic 9,5 t
027AX	extended radiator and intercooler over 35 degrees ambient temperature
028FP	rear springs parabolic 16 t
028PA	Fit tandem axles
029GC	Propshafts for high load profile
03KAA	fuel tank fitted
030EE	steering wheel with height and inclination adjustment
032AB	MAN BrakeMatic (electronic brake system)
034EC	brake shoe width for rear axle 220 mm
034MH	hub-reduction rear axle HPD-1382/ HP-1352
035KK	Planetary axle ratio $i = 3.63$
037AC	with differential lock in rear axle
038GH	disc wheels 10 hole 11.75-22.5 on 1st FA TL
038JH	disc wheels 10-hole 11.75-22.5 on 2nd front axle TL
038PG	disc wheels 10-hole 9.00-22.5 on 1st RA TL
038RG	disc wheels 10-hole 9.00-22.5 on 2nd RA TL
038TG	disc wheel 10-hole 9.00-22.5 as spare wheel TL
042CY	EC tachograph electronic, automatic, 2 drivers
05NAE	front panel unlockable from inside
050NN	M cab 2240mm wide, 1880mm long
052XA	without stowage boxes
058BA	seat coverings in standard quality
058NH	driver's seat, high-comfort, with air suspension
059NA	co-driver's seat static, with longitudinal + seat back adjustment
064AC	two additional vehicle keys
080AE	door interior panelling washable
116AE	visco fan
116AZ	Fan control for use in hot countries
118AC	air deflector to stop dust swirling
118EK	Short mounting base (engine only)
118MA	EDC engine regulation
119EH	General PTO parameterisation

122QH	PTO NH/1C without flange f=0.91/1.09right side, horizontal
123CC	strainer for fuel tank
124AL	fuel filter
124AZ	Auxiliary fuel filter with water separator
150WR	Brushed aluminium insert on instrument panel
153KA	air conditioning system AC R134A without CFHC
159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
194AC	operator's manual in French
201AR	air intake upswept with dry air filter / precleaner
201EM	Air filter cartridge with safety insert for heavy-duty deployment
201FA	fine dust and pollen filter
203EK	connection for external engine speedcontrol (ZDR)
205AN	air compressor 1-cylinder, 360 ccm
206EY	exhaust on rh side with tail pipe to rear
208AK	exhaust valve brake
210XX	Without flame-start/jump-start system
211FJ	Single-disc clutch DTE 430
227AC	rear axle breather upswept
230AH	rear underride guard, round
230ER	front underride guard
230YX	without lateral underride guard
232HA	synthetic bumper with integrated airdam
234AX	towing coupling ROCKINGER SK5
236AF	cross member for trailer coupling
241AC	without platform mounting brackets
245AE	spare-wheel holder on left side
256AA	steering wheel lock
256EA	emergency steering pump
258HA	anti-lock braking system (ABS)
259CA	disc brake for front axle
259CE	drum brake for rear axle
262XX	without brake connection on frame end
272FA	Entry lighting for driver and co-driver
280EC	Fly mesh guard before radiator
283FB	Cab mounts on coil springs for 'M' cab
303AM	Lockable tank cap - one unit, ventilated (cannot be approved/registered in accordance with ECE-R34)
310EE	Halogen twin headlights H7 for right-hand traffic
310FA	2 spotlights on cab roof
318AA	marker lamps
318AK	lateral marker lights
319AR	reading lamp for driver
321EC	central locking
324AC	Two-tone horn,electric

324CA	Two compressed air horns on the cab roof/roof spoiler
325AA	MAN Tronic (on-board computer)
325EE	Language 1 'French' for display in instrument panel
326XY	Without 12/24 V socket on end of frame
327AF	battery main switch, mechanical
329CS	Two 12-V 155-Ah batteries
329ER	Battery box up to 175 Ah
329HC	Maintenance sign for batteries - 'maintenance-free'
331AB	Basic alternator
339FP	Display on the dashboard for operating data
343AN	Acoustic warning system at end of frame for engaged reverse gear
345AU	Maximum electronic speed limitation 89 km/h
345EA	cruise control
346CA	charging pressure indicator
350NN	MAN Media Truck radio, 12 V with five-inch colour display
350XO	Without navigation SD
352FD	Preparation for installation of flashing beacons
362AH	Stabiliser on both rear axles
363AA	Stabiliser for front axle
363AE	Stabiliser on 2nd front axle
370CM	air dryer
373AE	antifreeze effective down to -35 degrees
376XH	Without Mattress for lower bunk
376XK	Without Mattress for upper bunk
376XL	No bunks for 'M' , 'C' , 'DK' cabs
380AC	windscreen of laminated glass tinted
380CA	door windows tinted
381AS	Cab rear wall with 2 tinted windows,centre and right
381XC	Without curtain before bunks
381YX	Without all-roand curtain
382AA	Grille on rear window
384CD	Safety belt display, driver's side
385AT	Side windows tinted behind B-post
386XA	Without lifting roof
387AF	Electric door window lifters for driver and co-driver
388AH	Roller blind for windscreen, mechanical
388AK	sun shade in front of windscreen
389AC	handles left and right (on B-post)
389AD	handles left and right (on A-post)
390XN	without waste paper bins between theseats
390XX	without oddment box
392AH	kerb mirror, right
392CL	EU front mirror on co-driver's side
392CZ	Electrically heated and adjustable rear view mirror, heated wide-angle mirror

392HA	Mirror brackets for body width 2500-2600 mm width 2500 mm
400AH	mudflap front
401CQ	Plastic mudguard rear (half-shell; without spray reduction)
401EL	3-part synthetic mudguards for 2nd front axle
404AP	spray reducer
405AC	Bonding set, separate
405AK	hazard-warning sign
405AR	hazard-warning lamp
405CP	20 m tyre inflator hose with pressure gauge
407AA	jack 25 t
411AA	1 chock
411AC	2nd chock
434CH	Smoking package
523AE	signs in French
523AM	signs additionally in Arabic
538AE	plastic floor and engine tunnel covering
542DM	Supplier declaration
542FX	anti-noise measures are not in accordance with EU standard
542HS	aprons in wheel houses to prevent soiling of the engine
600AC	Fittings for right-hand traffic
798LF	Height over cab, unloaded up to 4000mm
LQW01	chassis in water-based paint
LVS01	chassis graphite black RAL 9011 matt
LVS02	wheels White aluminium acrylic RAL 9006
LVS03	cab Pure white RAL 9010
80001	2 wahlweise 385/65R22,5 LENK-FERN TL
80002	2 wahlweise 385/65R22,5 LENK-FERN TL
90001	4 wahlweise 315/80R22,5 ANTR-S+G TL
90002	4 wahlweise 315/80R22,5 ANTR-S+G TL
90004	1 wahlweise 315/80R22,5 ANTR-FERN TL

Weights:

Gross weight: 41000

1st front axle: 8000

2nd front axle: 8000

3rd front axle: 0

Leading axle: 0

1st rear axle: 13000

2nd rear axle: 13000