

MAN TGS 33.360 6X4 BB-WW

Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005NW		wheelbase 3900+1400 mm
006CI		rear frame overhang 800 mm
018SJ		engine D2066LF07 - 360 hp / 265 kW EURO2 - 1800 Nm Common-Rail
02AAG		Instrument panel km/h 'High-Line in colour'
022WO		Gearbox ZF 16 S 253 OD
023EH		fuel tank 400l right
023VA		smaller ground clearance because of fuel tank
025MK		front axle VO-09 straight
026EC		front springs parabolic 8.0 t
027AX		extended radiator and intercooler over 35 degrees ambient temperature
028EC		rear springs parabolic 13 t
028PA		Fit tandem axles
029GC		Propshafts for high load profile
03KAA		fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034EC		brake shoe width for rear axle 220 mm
034MH		hub-reduction rear axle HPD-1382/ HP-1352
035LF		Planetary axle ratio $i = 4.33$
037AC		with differential lock in rear axle
038GG		disc wheels 10 hole 9.00-22.5 on 1stFA TL
038PG		disc wheels 10-hole 9.00-22.5 on 1stRA TL
038RG		disc wheels 10-hole 9.00-22.5 on 2ndRA TL
038TG		disc wheel 10-hole 9.00-22.5 as spare wheel TL
042XY		without electronic tachograph
05NAE		front panel unlockable from inside
050NN		M cab 2240mm wide, 1880mm long
052XA		without stowage boxes
058BA		seat coverings in standard quality
058NE		driver's seat static, longitudinal, seat back and height adjustment
059NA		co-driver's seat static, with longitudinal + seat back adjustment
080AE		door interior panelling washable
116AE		visco fan
118AC		air deflector to stop dust swirling
118EK		Short mounting base (engine only)
118MA		EDC engine regulation

119EH		General PTO parameterisation
122QN		PTO NH/4C without flange f=1.17/1.40right horizontal
123AC		guard plate for 1 tank
123CC		strainer for fuel tank
124AL		fuel filter
124AZ		Auxiliary fuel filter with water separator
150WR		Brushed aluminium insert on instrument panel
153KA		air conditioning system AC R134A without CFHC
159XS		without cab insulation NORDIC (against cold) for M, L and LX cab
194AC		operator's manual in French
194EA		additional operator's manual in ENGLISH
201AR		air intake upswept with dry air filter / precleaner
201EM		Air filter cartridge with safety insert for heavy-duty deployment
201EY		Cyclone filter on front panel for cab fresh air mode
201FA		fine dust and pollen filter
203EK		connection for external engine speedcontrol (ZDR)
203ER		Control module for external data exchange (customer-specific control module) with body functionality
205AN		air compressor 1-cylinder, 360 ccm
206ET		exhaust on lh side with tail pipe towards rear
208XD		without exhaust valve brake (EVB)
210XX		Without flame-start/jump-start system
211FQ		Single-disc clutch DTE 430, reinforced
227AC		rear axle breather upswept
230XW		Without front underride guard
230XX		Without rear underride guard
230YX		without lateral underride guard
233EM		3-part steel bumper
234AX		towing coupling ROCKINGER SK5
236AF		cross member for trailer coupling
241AH		body attachment brackets bolted
245AE		spare-wheel holder on left side
256AA		steering wheel lock
258HA		anti-lock braking system (ABS)
259CC		drum brake for front axle
259CE		drum brake for rear axle
262AC		brake connection 2-line
272FA		Entry lighting for driver and co-driver
280EU		stoneguard grille in front of radiator
281AB		medium-height design
283FB		Cab mounts on coil springs for 'M' cab
303AM		Lockable tank cap - one unit, ventilated (cannot be approved/registered in accordance with ECE-R34)
310EE		Halogen twin headlights H7 for right-hand traffic

311AA		protective grille for headlights headlights
311AE		protective grille for taillamps
318AA		marker lamps
318AK		lateral marker lights
319AR		reading lamp for driver
321EC		central locking
324AC		Two-tone horn,electric
325AA		MAN Tronic (on-board computer)
325EE		Language 1 'French' for display in instrument panel
325FC		Language 2 'English' for display in instrument panel
326CK		trailer socket for anti-skid system on frame end
326CN		15-pin 24 V trailer socket on end of frame
327AF		battery main switch, mechanical
329CS		Two 12-V 155-Ah batteries
329ER		Battery box up to 180 Ah
329HC		Maintenance sign for batteries - 'maintenance-free'
331AB		Basic alternator
339FP		Display on the dashboard for operating data
343AN		Acoustic warning system at end of frame for engaged reverse gear
345CV		Maximum electronic speed limitation 85 km/h
345EA		cruise control
346CA		charging pressure indicator
350NN		MAN Media Truck radio, 12 V with five-inch colour display
350XO		Without navigation SD
351US		AUX-IN/USB in the instrument panel
352CF		2 halogen revolving beacons on cab roof left and right
352WS		Revolving beacon, yellow
362AH		Stabiliser on both rear axles
363AA		Stabiliser for front axle
370CM		air dryer
373AE		antifreeze effective down to -35 degrees
376XH		Without Mattress for lower bunk
376XK		Without Mattress for upper bunk
376XL		No bunks for 'M' , 'C' , 'DK' cabs
380AC		windscreen of laminated glass tinted
380CA		door windows tinted
381AA		cab rear wall without windows
381XC		Without curtain before bunks
381YX		Without all-round curtain
385AT		Side windows tinted behind B-post
386XA		Without lifting roof
387AF		Electric door window lifters for driver and co-driver
388AH		Roller blind for windscreen, mechanical
388AK		sun shade in front of windscreen

389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390CT		cup holder in dashboard
390XX		without oddment box
392AH		kerb mirror, right
392CZ		Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
392XJ		Without front mirror on co-driver's side/at centre
394FE		1 French fire extinguisher, 2 kg to 1996 safety regulations
400AH		mudflap front
401AS		mudguard cover for transfer
401CQ		Plastic mudguard rear (half-shell; without spray reduction)
404AP		spray reducer
405AC		Bonding set, separate
405AK		hazard-warning sign
405AR		hazard-warning lamp
406ED		lock for battery box
406FB		lock for spare wheel carrier
407AA		jack 25 t
411AA		1 chock
434DA		Interior design in Sand
523AE		signs in French
538AE		plastic floor and engine tunnel covering
542FX		anti-noise measures are not in accordance with EU standard
542NC		Registration as N3 vehicle, (GVW > 12t)
600AC		Fittings for right-hand traffic
798CP		miscellaneous Gervasi Hinterkipper
798LF		Height over cab, unloaded up to 4000mm
798RA		Body mounting/conversion in acc. with Truck Request. TR number: R1.18015.5528
798WK		vehicle can be registered only as off-road vehicle to directive 70/156/EEC; note body
LQN03		Cab, standard quality
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab Pure white RAL 9010
80001		2 wahlweise 315/80R22,5 LENK-S+G TL
90001		4 wahlweise 315/80R22,5 ANTR-S+G TL
90002		4 wahlweise 315/80R22,5 ANTR-S+G TL
90004		1 wahlweise 315/80R22,5 LENK-S+G TL

Weights:

Gross weight: 33000

1st front axle: 7500

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 13000

2nd rear axle: 13000